

Newage Fire Hose Pipe 63 mm x 15 m (Type 1, 2, 3 Non-Percolating)

Brand: Newage

Newage non-percolating fire hose pipe, 63 mm x 15 m, in Type 1 (Premier), Type 2 (Premier Extra) or Type 3 (Pyroprotect) with gunmetal or SS couplings.

SPECIFICATIONS

Size	63 mm (2 1/2 inch) x 15 m
Construction	Non-percolating, rubber lined, synthetic woven jacket
Type 1 (Premier)	Polyester jacket, EPDM lining; working pressure 15 bar
Type 2 (Premier Extra)	Plus elastomer outer coat; working pressure 12 bar
Type 3 (Pyroprotect)	Ribbed rubber cover, polymer lining; working pressure 17 bar
Couplings	63 mm instantaneous, male + female, gunmetal or SS-304
Standard colour	Type 1/2: red; Type 3: reddish brown

Specifications as published by the manufacturer (Newage). They may change without notice.

AVAILABLE OPTIONS

Hose Type	Coupling
Type 1 (Premier)	GM Coupling
Type 1 (Premier)	SS Coupling
Type 2 (Premier Extra)	GM Coupling
Type 2 (Premier Extra)	SS Coupling
Type 3 (Pyroprotect)	GM Coupling
Type 3 (Pyroprotect)	SS Coupling

WHICH ONE DO I NEED?

Type 1 (Premier)	Indoor hose boxes in offices and homes
Type 2 (Premier Extra)	Basements, parking, outdoor hydrants
Type 3 (Pyroprotect)	Refineries, plants, rough yards

Ask us for a recommendation for your site.

Order or get a quote

Call / WhatsApp: (+91) 72 4747 6161
Email: sales@safetycart.in

Dispatch within 7 days

Pan-India delivery
GST invoice on every order