

Newage Foam Making Branch Pipe (FB5X 225 LPM, FB10X 450 LPM)

Brand: Newage

Newage foam making branch pipe with a built-in foam inductor and pick-up tube, in FB5X (225 LPM) and FB10X (450 LPM), for oil and fuel fires.

SPECIFICATIONS

Type	Low expansion, air-aspirating foam branch pipe
Models	FB5X: 225 LPM; FB10X: 450 LPM (at 7 bar)
Throw	About 15 m (FB5X); about 18 m (FB10X)
Foam inductor	Built-in, with pick-up tube and dip pipe
Proportioning	0 to 6%
Expansion ratio	1:2 to 1:10
Inlet	63 mm male instantaneous
Construction	Aluminium alloy tube, cast bronze inlet; max 10 kg/cm ²

Specifications as published by the manufacturer (Newage). They may change without notice.

AVAILABLE OPTIONS

Model
FB5X (225 LPM)
FB10X (450 LPM)

WHICH ONE DO I NEED?

FB5X (225 LPM)	Fuel stations, pump rooms, small spills
FB10X (450 LPM)	Tank areas, bunds, loading bays

Ask us for a recommendation for your site.

Order or get a quote

Call / WhatsApp: (+91) 72 4747 6161
Email: sales@safetycart.in

Dispatch within 7 days

Pan-India delivery
GST invoice on every order